

2019 SWARTZ PROMOTIONS

CARLYLE, IL - SATURDAY JULY 20TH AT 7PM

AUTOCROSS 2019

FULL SIZE

1ST \$200

2ND \$100

3RD \$50

MINI-CAR 108" WHEELBASE OR LESS

1ST \$200

2ND \$100

3RD \$50

MINI-CAR RULES 2019

108" WHEELBASE OR LESS

PAYOUT:

1ST \$700

2ND \$400

3RD \$300

4TH \$200

5TH \$100

With 30 plus cars payout is as follows:

1st \$1200

2nd \$600

3rd \$300

4th \$200

5th \$100

ALL JUDGES DECISIONS ARE FINAL!!!

Please read carefully. If car does not pass inspection or driver is unwilling to change car to pass inspection, absolutely no refunds!!! All rules will be followed or you will not run! If it does not say it in the rules – don't just assume you can do it. **CALL FIRST!!!!**

THE COUNTY FAIR HAS THE RIGHT TO REFUSE ANY ENTRY AND SPECTATOR ADMITTANCE.

1. Pit gate opens at 3 pm Derby starts at 7 pm

2. An entry fee of \$40 will be charged for each car entered. \$30 for passenger. \$25 for pit passes Fees must be paid prior to inspection. **NO REFUNDS WILL BE MADE DUE TO FAILURE TO MEET REGULATIONS!** All cars should be signed in 1 hour before race time and inspected one hour before race time. Late fee will apply, example after 6:00 pm, if show starts at 7:00 pm and 2:00 pm if the shows starts at 3:00 pm. drivers \$100 and riders \$50. This is to ensure the race starts on time.

PLEASE READ THESE THROUGHLY AND COMPLETELY. 2019 IS A NO EXCUSE AND NO EXCEPTION YEAR!!

NO REFUNDS WILL BE MADE DUE TO FAILURE TO MEET REGULATIONS!

2019 CHANGES ARE IN RED

GENERAL RULES

3. Top five in feature must actively compete at end, no driving yourself on barriers or dirt berms. Failure to comply could result in complete restart with all feature qualifiers actively competing again or disqualification.
4. No reinforcements allowed other than specified in these rules. Any metal added to reinforce the car is illegal. You will only be allowed 2 trips thru the inspection line.
5. NO PAINTING, UNDERCOATING, OILING OR GREASING OF FRAMES. YOU WILL NOT BE INSPECTED. THIS INCLUDES PAINTING OF THE FRAME FLAT BLACK.
6. NO HITTING IN DRIVERS DOOR, but no using driver door as a shield. If the hit is deemed by the official to be careless or intentional, you will be disqualified. If you use your driver's door as a defense, we will not enforce the rules. If you use the door as a defense repeatedly you will be disqualified. This will be at the judges' discretion.
7. NO hot-rodding in the pits! Keep it at an idle.
8. Any open door or second fire will cause disqualification. If in a heat, you may fix it and come back in the consolation. In the feature, you will be disqualified.
9. You must make AGGRESSIVE contact every 60 seconds.
10. Sandbagging is not tolerated and will be strictly enforced. Locking up the brakes prior to a hit for anything other than a driver's door will be cause for disqualification. The fans pay to see a show, put one on for them!
11. IF YOU THINK SOMEONE IS SANDBAGGING, HIT THEIR CAR WITH YOUR CAR ON THE TRACK.
12. Winning cars plus three out of the money must remain on track until released by officials, or will not be paid prize money. Cars are subject to re-inspection before any prize money is handed out. Cars found illegal will be stripped of all prize money for that event.
13. Any questions or controversies will be discussed at the drivers meeting
14. YOU MUST HAVE AT LEAST A 12" X 12" ROOF SIGN WITH YOUR CAR NUMBER ON IT.
15. All drivers must pick up trophies and earnings at the completion of the event, or forfeit. They will not be available after that date.
16. All persons MUST sign entry form, insurance waiver, release form, pay entry fees, and purchase pit pass before entering pit area.
17. THERE IS NO ALCOHOL IN THE PITS. This includes pit crews. If you or ANY of your crew is caught with alcohol, you will be disqualified.
18. No harassing of the judges will be allowed at any time by drivers, passengers, crewmembers or spectators. Failure to abide by this rule, the driver will forfeit all money and all involved will be escorted from premises.
19. Registration forms will be filled out the day of the event. All drivers must be at least 16 years of age; drivers 16 and 17 must have a parent or legal guardian sign a minor release form
20. All drivers must wear approved helmets, eye protection either safety glasses or visor on helmet, long pants, and shirt. Also all drivers and riders must wear working seat belts. This will be enforced in 2019 or you will not run!!!!
21. - Drivers must remain in the vehicle with helmet, seatbelt and eye protection on until notified by an official that it is safe to exit the vehicle.
22. A driver that receives a black flag for an intentional door hit will be disqualified from all competition

for that night. A driver that receives a black flag for sandbagging or 1 fire in the interior of the car will be disqualified. 2 fires on the exterior will be disqualified, if in heat you may go to consolation. This will be at the judges' discretion.

23. This is not a team event; team driving will not be tolerated

24. All drivers must attend drivers' meeting prior to derby

25. All cars must be removed from derby site by 12:00 noon the following day unless otherwise stated at drivers meeting. Failure to do this will result in cars being removed by and becoming property of Fair Board.

26. DO NOT READ ANYTHING INTO THESE RULES, JUST READ THE RULES!! If it doesn't say you can, YOU CAN'T!

27. DO NOT paint anywhere on suspension or frame; if we can tell it's been painted, we will not even inspect your car.

28. ALL SUNROOFS MUST BE COVERED WITH A THIN SHEET OF METAL, I.E. WELED OR BOLTED (WITH BOLT HEAD INSIDE THE CAR) OR RIVETED. NO # 9 wire or chain to accomplish this will be allowed.

2019 MINI-CAR RULES 108" WHEELBASE OR LESS

1. Must be powered by four or six cylinder engine

2. Wheelbase must be 108 inches or less. NO EXCEPTIONS!

A. NO moving/bending a stock or aftermarket component to shorten wheel base.

3. No four-wheel drive vehicles.

4. MANDATORY! All four/six cylinder cars must have a cage. Four point minimum.

5. Stock gas tank MUST be removed. A METAL BOAT TANK OR HOMEMADE METAL TANK must be mounted in rear seat area and bolted down with metal straps. NO PLASTIC TANKS!!!

A. Battery and gas tank must be tight when coming through inspection line or you wont be inspected.

6. All lines under car must be steel lines or if running rubber lines they must be inside of the car.

7. If OEM bumper had no bolts bumper homemade bumper brackets may go six (6) inches from back side of bumper.

8. No pipe over struts.

9. No kickers

10. No aftermarket or homemade extreme cradle/pullet protector

ALL JUDGES DECISIONS ARE FINAL

1. Cars previously run in Demolition Derby may install new front clip. Any clip may be used on any car, MUST be installed in stock manner. Officials MUST approve installation.

2. All glass, side windows, rear windows, headlights and taillights, must be removed before reaching racetrack. Rolling down windows is not permitted. . Remove all glass mirrors and plastic. Remove all decking in wagons. Vehicles must be swept clean of all debris

3. Rear seat of sedan must be removed, top and bottom. On station wagons all seats and decking must be removed. Station wagons must be emptied to floorboards. All cars must be swept clean, both drivers compartment and trunk. No spare tires, broken glass, or trash, etc., allowed in cars.

4. Cars must have a seatbelt and working brakes. MANDATORY!!

5. You can carry a fire extinguisher, but it must be mounted securely and free of movement.

6. Battery may be moved, but must be securely fastened and covered in passenger compartment.

MAXIMUM OF TWO AUTOMOBILE TYPE BATTERIES ALLOWED. Battery and gas tank must be tight when coming through inspection line or you wont be inspected.

7. Any type automotive radiator may be used but must be mounted in stock position. NO RESERVE TANKS. A radiator cradle is allowed made of 1/8" metal 1" wider than the radiator. Bolted only to car and nothing in front of the radiator. AFTERMARKET OR HOME MADE RADIATOR CRADLE.

A. Front rad. screen max. Thickest 3/8" thick, bolted or 4 1" welds.

8. Fenders may be bolted together with 3/8 inch bolts or smaller with 3/8 inch or smaller washers only. A maximum of 10 bolts per fender.

9. All doors may be welded (Outside of body only), chained or wired. Straps cannot be larger than 1/4" thick and 4 inches wide on door shell (vertical) and 2 inches wide on window frame. You may beat top of doors down and may tack them in three places with a maximum of 1" weld each.

10. No doubling of body panels allowed, no added metal allowed.

11. Patching floorboards, if you have to patch rusty floorboards you must cut out all the rust, overlap no more than 1" with same thickness as body material and sheet metal screws – no more than one every 4". No Welding to floorboards or firewall.

12. You may crease/enhance sheet metal body panels but do not fold and weld. No extra metal may be added.

13. NO OTHER BODY WELDS OTHER THAN WHAT IS LISTED ABOVE. THIS INCLUDES BODY SEAMS ANYWHERE ON THE CAR.

14. ALL SUNROOFS MUST BE COVERED WITH A THIN SHEET OF METAL, I.E. WELED OR BOLTED (WITH BOLT HEAD INSIDE THE CAR) OR RIVETED. No #9 wire or chain to accomplish this will be allowed.

HOODS AND TRUNKS

MUST BE OPEN AT INSPECTION! So don't come to inspection line with hood bolted down....

1. **HOODS:** must have two (2) holes, at least four (4) inches in diameter on each side of carburetor – Not directly on top of carburetor. IF HOOD IS REMOVED, EITHER FAN BLADE MUST BE REMOVED OR FAN BELT MUST BE CUT.

2. NO SECOND ALL THREAD WELDED TO SIDE OF THE FRAME AND RAN THROUGH THE AT MID POINT OF THE HOOD.

3. On all cars, hoods, trunks, and tailgates may be secured with the following method: on front of car, two pieces of 1 inch all thread, NO SLEEVING, Can have a 4" or less spacer free floating or welded between core support and frame, with a washer no larger than six (6) inches O.D. and 3/8 inch thick, all threads MUST be mounted outboard of the radiator. In addition to all threads, six (6) 1 inch O.D. bolts with a washer no larger than six (6) inches O.D. and 3/8 inch thick, or you may use angle iron back to back with a bolt through it. Angle iron cannot be more than 3/16 thick or longer than 6 inches. Three on each side of car, a total of six. Total of 6 bolts and 2 up front all threads holding the hood down and any amount of wire or cable. All wire, or cable MUST be mounted outboard of radiator. A maximum of 20 bolts 3/8 inch or smaller are allowed to bolt together hood seams.

TRUNK 4 pieces of 5/8 inch all thread, with a washer no larger than six (6) inches O.D. and 3/8 inch thick, all threads may be mounted through deck lid and frame anywhere in trunk, can be welded to the frame or in body mount holes. In addition to all threads, you may weld trunk 5 on 5 off, Straps should not be larger than 1/4" thick or 4 inches wide or six (6) 1 inch O.D. bolts with a washer no larger than six (6) inches O.D. and 3/8 inch thick, or 10 3/8" bolts in the drip rail, not both one or the other and any amount of wire or cable. If trunk is welded must have a 12" hole in trunk lid. On station wagons two

pieces of 1 inch all thread, with a washer no larger than six (6) inches O.D. and 3/8 inch thick, all threads may be used in the rear through roof and stock body mount replacing existing bolt.

TAILGATE weld 5 on 5 off, Straps should not be larger than 1/4" thick or 4 inches wide or six (6) 1-inches O.D. bolts with a washer no larger than six (6) inches O.D. and 3/8 inch thick, and any amount of wire or cable. **YOU CAN WELD WASHERS** (no bigger than 5/8 washer and must be at least 12" apart) **TO THE BODY TO RUN WIRE THROUGH.**

A. No carburetor protector outside the intake area or DP.

B. You may have rear window bar 2"X2"X1/4" MAX. IN SIZE, 6" max. on roof 4"X4"X1/4" FLAT PLATE TO ATTACH TO THIS BAR TOP AND BOTTOM and must be centered on front side drip rail on trunk no further back (2" on each side). Weld to the strapping on your trunk. There must be 6" minimum distance (gap) from the top of this bar on the roof and halo bar.... This is the only location allowed for this bar.

BODY MOUNTS

1. All body mount bolts may be replaced with 1/2 inch O.D. bolts with a stamped washer. Do not take them out and place body on frame. If replaced, a gap of 1" minimum is mandatory between body and frame. You may replace with a stack of washers, or one piece of anything solid, as long as it is about the same diameter as the factory bushing. Do NOT crush factory body bushings. Body mount bolts inside passenger compartment that are close together may have one washer six (6) inches x twelve (12) inches, must have two (2) or more body mount bolts through washer. You may add two (2) additional body mount bolts per side inside passenger compartment. All all-threads MUST have nut on top and bottom and NO welds.

4. A minimum of one chain or wire running from the outside (top) of roof down to the cowl or BAR DOWN TO DASH BAR OF CAGE on the front window is MANDATORY for safety. Maximum of two. IF YOU HAVE A PASSENGER MUST HAVE 2. IF USING METAL STRAPS MAX. SIZE 2" WIDE X 1/4" THICK, 12" ID APART. CAN GO TO FRONT DASH BAR OR COWL THEN TO TOP LIP AREA OF WINDSHIELD ONLY.

CAGE AND HALO BARS

1. All driver and passenger doors may be reinforced. You should have a six (6)-point cage, MINIMUM OF A 4PT. CAGE. cross bars may be ran as follows, one across dash, one behind front seats, and one in rear seat area, 3rd bar must stay inside of interior of rear drivers compartment nothing past front of package tray. Nothing can be added to the bottom of this bar.

2. You can run four (4) down tubes, two (2) per side. 2 of these down tubes must mounted mandatory in the following way on each side, 1 down tube must be to flat part of the frame no further forward then the inner front door seam, with a max distance of 2' from the same measuring point. Lower door bars are allowed between down tubes must be 6 inches or more above top of frame. NOTHING OUT OF DRIVERS' COMPARTMENT. You can have steel plate between cage and front doors. Must be securely fastened to cage. Front bar must be mounted no more than 2" below the bottom of the front window seal and be no more than 4" in diameter. Must have 6" between front bar and center of firewall on a fresh car. Front bar cannot be attached to firewall at any time. ALL DOWN TUBES MUST BE BEHIND DASH BAR, STRAIGHT UP AND DOWN AND ON FLAT PART OF FRAME. CAN NOT GO TO BODY MOUNT BOXES. NO KICKERS TO REAR HUMPS. NOTHING OUT OF REAR DRIVERS COMPARTMENT. You cannot weld anything to front bar protruding toward the distributor protector. No grater blades, metal plates or tubing on exterior of body (driver & passenger doors).

3. DP can't touch dash bar during or at the end of the derby or you will be disqualified.

4. Halo bars are allowed. Can be attached to bar behind your seat or could be run to the frame but it would be counted as one of your down tubes. There must be 6" minimum distance (gap) from halo bar and the top of your rear window bar....Nothing can be attached to halo bar
5. This is not mandatory but we encourage everyone to put a steel plate between cage and front driver and passenger doors. Thickness of metal is up to driver. Must be securely attached to cage, must be 2" off of floor, this is for protection not reinforcement.

FRAME

1. DO NOT REWELD ENGINE CROSS MEMBER SEAMS OR ANY OTHER BRACKETS ATTACHED TO FRAME OR SHEET METAL under hood or trunk. NO CONCRETE!!! DO NOT WELD FACTORY HOLES UP; ALL FACTORY HOLES MUST BE OPEN FOR INSPECTION OF FRAME.
2. You cannot alter frame in any way other than specified in rules. Do not crease or reshape frame.
3. You may run one (1) wire or chain from frame rail to frame rail underneath back of car behind back tires/wheels.
4. You may put a bolt with a stamped flat washer thru frame to hold it together. Only one (1) per wheel opening must be loose during inspection. DO NOT weld washer. (Pinning of frame)
5. You may notch the frame for minimal pre-bending, but do NOT weld the cut.
6. If changing front stub, cut 3 inches behind second cross member bolt hole. When replacing, can overlap 2 ½", able to weld both sides, but no adding extra metal. Must be of the same make and model.
7. If restubbing one side of the frame, you are allowed to cut and fit the new frame flush and weld one pass all the way around (butt – fit – weld). Must be of the same make and model.
8. All trailer hitches MUST be totally removed.
9. 2019 THIS INCLUDES MINI'S: If running a used car prior to this derby, you are allowed 4 patch plates max. Size 4"x4"x1/4". Must be painted a bright color. So it is easily noticed for the inspectors. AFTER INSPECTION OR HEATS NO WELDING THESE PLATES ON. IF ADDITIONAL PLATES ARE FOUND AFTER INSPECTION – NO MONEY WILL PAID OUT
- 10. Attachment of lower front sub frame to body, can use only chain 3/8" or smaller, can weld the links at each end for attachment points. But on a used/preran car you can use a metal strap, but each one counts toward/as your patch plates**
11. No plates on fresh cars to fix/patch rust holes, unless it's a preran/used car then follow patch plate rule.

BUMPERS

1. Any OEM shock canister may be bolted or welded to any car. AMOUNTS OF BOLTS OR WELDS MAY NOT EXCEED TYPICAL STOCK INSTALLATION. Homemade bumper brackets are permitted, NO GUSSETS OR BRACING. NOT TO EXTEND BEHIND OEM MOUNTING BOLT LOCATION ON FRAME. May use 2½" max. Round or square tubing. No thicker than ¼ inch. No solid stock may be used. This can only extend into the frame a max. of 8". Will be drilled at 8 ¼" measured from the front edge of the frame on every car. Any OEM stock automobile bumper may be bolted or welded to the shock canister or bumper brackets. You may use two (2) pieces of light chain per shock. Fenders and bumper ends may be trimmed to allow for wheel clearance.
2. Front bumper may be reinforced inside or behind and end to end. Must have chrome on the outer part of the bumper from any OEM bumper shaped to fit. You may weld outer chrome of bumper to inner skin of bumper. Nothing else can be welded to outer chrome. You cannot alter angle of bumper.

Anything coming out of bumper during race will be cause for disqualification. 11" of point and must contour from frame to frame and must be stock appearing on pointy bumpers. (the curve of point must start at each frame)

3. You may have 6" long 4" wide 1/4" thick bumper support bracket, butt fit against bumper or 2" onto bumper. If you're running a preran and choice to put your extra. 4 by 4 1/4" plate up front there must be at least a 1/8" gap between the 2 plates. Any questions please call.

4. No front bumper straps to core support or all thread.

SUSPENSION

1. Stiffness of suspension will be left up to the discretion of the driver. NO OTHER METAL ADDED!

2. Homemade tie rods and homemade steering shaft are permitted.

3. No pipe over struts

ENGINE AND TRANSMISSION

1. ANY ENGINE OR TRANSMISSION MAY BE USED IN ANY FRONT WHEEL DRIVE CAR, BUT MUST BE MOUNTED IN A STOCK POSITION.

2. Chained, welded, or homemade motor mounts will be permitted, but must meet approval of officials.

3. At motor mount to sub-frame your allowed 2 per side of motor mount a 2"x3"x1/4" plate on its side welded to frame and engine cradle

4. Any type of header is allowed, but must be directed away from driver compartment.

5. Transmission oil coolers and engines oil coolers are permitted. Inspection personnel must approve all mountings, lines, and fittings.

6. Skid plates are allowed. Must be separate oil/transmission plates. No full-length skid plates. No bolting or welding to frame.

7. Distributor protectors are allowed. Cannot be any wider than 12" and must not protrude more than 2" from transmission mounting surface on back of engine block. Must be attached to engine or transmission mounting bolts.

8. No aftermarket or homemade extreme cradle/pullet protector

9. No carburetor protector outside the intake area or DP. *No aftermarket or homemade attachments to rad. Core support or fire wall. Nothing outside of the normal/factory type attachment points.

10. You may beat flat the engine side of the firewall only, do not weld or bolt firewall. Do not re-enforce the firewall/cowl. Do not beat, paint, bolt, weld on, weld to or modify the driver's side of the firewall/cowl in any way.

11. Transmission protectors are allowed. MUST FLOAT OVER CROSSMEMBER

12. Must have stock/OEM cross member

GAS TANKS

Battery and gas tank must be tight when coming through inspection line or you won't be inspected.

1. Stock gas tank MUST be removed. A METAL BOAT TANK OR HOMEMADE METAL TANK must be mounted in rear seat area and bolted down with metal straps. Other types of installations will not be allowed. NO GAS CANS with hoses duct taped. A Marine (boat) tank or an official approved homemade tank is mandatory. All tanks MUST be covered with a rubber cover. All tanks MUST have secure cap. All lines and fittings MUST be leak proof and meet approval of Officials. Electric fuel pumps are permitted but MUST have shut-off within reach of driver. NO MORE THAN ten (10) GALLONS OF GAS IN TANK.

2. NO PLASTIC TANKS, unless in a wooden box 1" thick minimum or a metal box ¼" minimum. All sides except top side. This also goes for if your using a metal boat tank.

3. Mounted in center of the back side area.

FOR THE MINI-CAR DERBY CLASS, YOU WILL NO LONGER BE ABLE TO MOVE THE STOCK GAS TANK INTO THE BACK SEAT AREA. For mini autocross only you can leave factory tank under the car.

REAR END

1. Any automobile rear end can be used in any car. You cannot transform a coil spring to leaf spring or vice versa. On models originally equipped with leaf springs, stock leaf springs and hangers MUST be used. Leaf packs on all cars may have no more than 8 leaves per pack Must be OEM stock. Homemade spring perches or homemade trailing arm brackets may be welded to rear end. Rear end spider gears may be welded solid. You may tilt rear end by shortening or lengthening rear end control arms. Trailing arms may be reinforced. Rear end housing may be reinforced. No dually wheels allowed..

2. Any drive shaft or U joint may be used. Welding of drive shaft is permitted.

3. No extra metal added. Any bracket that shows reinforcement to the frame will not be allowed.

JUDGES HAVE FINAL DECISION. .

TIRES

1. Only sixteen (16) inch or smaller tires and wheels will be allowed. NO SPLIT RIMS ALLOWED.

2. Valve stem protectors, liquid in tires permitted or screws in rims to hold tires in place permitted.

ALL JUDGES DECISIONS ARE FINAL

Any questions contact: Randy Schwartzkopf at [618-218-0203](tel:618-218-0203) call or text or at

Randyschwartzkopf@gmail.com

STOCK RULES 2019

[/font]PAYOUT:

1ST \$1650

2ND \$800

3RD \$400

4TH \$350

5TH \$200

6TH \$100

PLEASE READ THESE RULES THOROUGHLY AND COMPLETELY

2019 IS A NO EXCUSE AND NO EXCEPTION YEAR!!!

ALL JUDGES DECISIONS ARE FINAL!!!

Please read carefully. If car does not pass inspection or driver is unwilling to change car to pass inspection, absolutely no refunds!!! All rules will be followed or you will not run! If it does not say it in the rules – don't just assume you can do it. CALL FIRST!!!!

ANY COUNTY FAIR HAS THE RIGHT TO REFUSE ANY ENTRY AND SPECTATOR ADMITTANCE.

1. Pit gate opens at 3 pm DERBY START at 7 pm

2. An entry fee of \$40 will be charged for each car entered. \$30 for passenger. \$25 for pit passes Fees must be paid prior to inspection. NO REFUNDS WILL BE MADE DUE TO FAILURE TO MEET REGULATIONS! All cars should be signed in 1 hour before race time and inspected one hour before race time. Late fee will apply, example after 6:00 pm, if show starts at 7:00 pm and 2:00 pm if the shows starts at 3:00 pm. drivers \$100 and riders \$50. This is to ensure the race starts on time.

NO REFUNDS WILL BE MADE DUE TO FAILURE TO MEET REGULATIONS!
IN RED ARE THE 2019 CHANGES

GENERAL RULES

3. Top five in feature must actively compete at end, no driving yourself on barriers or dirt berms. Failure to comply could result in complete restart with all feature qualifiers actively competing again or disqualification.

4. No reinforcements allowed other than specified in these rules. Any metal added to reinforce the car is illegal. You will only be allowed 2 trips thru the inspection line.

5. NO PAINTING, UNDERCOATING, OILING OR GREASING OF FRAMES. YOU WILL NOT BE INSPECTED. THIS INCLUDES PAINTING OF THE FRAME FLAT BLACK.

6. NO HITTING IN DRIVERS DOOR, but no using driver door as a shield. If the hit is deemed by the official to be careless or intentional, you will be disqualified. If you use your driver's door as a defense, we will not enforce the rules. If you use the door as a defense repeatedly you will be disqualified. This will be at the judges' discretion.

7. NO hot-rodding in the pits! Keep it at an idle.

8. Any open door or second fire will cause disqualification. If in a heat, you may fix it and come back in the consolation. In the feature, you will be disqualified.

9. You must make AGGRESSIVE contact every 60 seconds.

10. Sandbagging is not tolerated and will be strictly enforced. Locking up the brakes prior to a hit for anything other than a driver's door will be cause for disqualification. The fans pay to see a show, put one on for them!

11. IF YOU THINK SOMEONE IS SANDBAGGING, HIT THEIR CAR WITH YOUR CAR ON THE TRACK.

12. Winning cars plus three out of the money must remain on track until released by officials, or will not be paid prize money. Cars are subject to re-inspection before any prize money is handed out. Cars found illegal will be stripped of all prize money for that event.

13. Any questions or controversies will be discussed at the drivers meeting

14. YOU MUST HAVE AT LEAST A 12" X 12" ROOF SIGN WITH YOUR CAR NUMBER ON IT.

15. All drivers must pick up trophies and earnings at the completion of the event, or forfeit. They will not be available after that date.

16. All persons MUST sign entry form, insurance waiver, release form, pay entry fees, and purchase pit pass before entering pit area.

17. THERE IS NO ALCOHOL IN THE PITS. This includes pit crews. If you or ANY of your crew is caught with

alcohol, you will be disqualified.

18. No harassing of the judges will be allowed at any time by drivers, passengers, crewmembers or spectators. Failure to abide by this rule, the driver will forfeit all money and all involved will be escorted from premises.

19. Registration forms will be filled out the day of the event. All drivers must be at least 16 years of age; drivers 16 and 17 must have a parent or legal guardian sign a minor release form

20. All drivers must wear approved helmets, eye protection either safety glasses or visor on helmet, long pants, and shirt. Also all drivers and riders must wear working seat belts. This will be enforced in 2019 or you will not run!!!!

21. - Drivers must remain in the vehicle with helmet, seatbelt and eye protection on until notified by an official that it is safe to exit the vehicle.

22. A driver that receives a black flag for an intentional door hit will be disqualified from all competition for that night. A driver that receives a black flag for sandbagging or 1 fire in the interior of the car will be disqualified. 2 fires on the exterior will be disqualified, if in heat you may go to consolation. This will be at the judges' discretion.

23. This is not a team event; team driving will not be tolerated

24. All drivers must attend drivers' meeting prior to derby

25. All cars must be removed from derby site by 12:00 noon the following day unless otherwise stated at drivers meeting. Failure to do this will result in cars being removed by and becoming property of Fair Board.

26. DO NOT READ ANYTHING INTO THESE RULES, JUST READ THE RULES!! If it doesn't say you can, YOU CAN'T!

27. DO NOT paint anywhere on suspension or frame; if we can tell it's been painted, we will not even inspect your car.

28. ALL SUNROOFS MUST BE COVERED WITH A THIN SHEET OF METAL, I.E. WELED OR BOLTED (WITH BOLT HEAD INSIDE THE CAR) OR RIVETED. NO # 9 wire or chain to accomplish this will be allowed.

2019 STOCK RULES ... JUDGES DECISION ARE FINAL

1. DO NOT READ ANYTHING INTO THESE RULES, JUST READ THE RULES!! If it doesn't say you can, YOU CAN'T! Or you will be loaded, your choice!

2. NO black cars, dark cars must have contrasting letter/numbers. DO NOT paint anywhere on suspension or frame; we will not even inspect your car.

3. Any year car EXCEPT No Imperials, no Suicide Lincolns, and no Hearses

4. Body components must be direct bolt up only. Must be factory hardware or equivalent in size

5. Remove all glass mirrors and plastic. Remove all decking in wagons

6. Vehicles must be swept clean of all debris

7. No sedagons, ZERO crease enhancements, ZERO sheet metal or frame shaping, forming or folding.

8. - Front Windshield Bar is MANDATORY and is limited to two 2" wide x 1/4" thick straps or two 3/8" chains or two strands of 9 wire. May be welded or bolted or both. 6 inches on roof and 6 inches on firewall for attachment. 12" apart measured I.D.

(1 min., with rider must have 2)

9. Fenders maybe bolted together with 3/8" or smaller bolts and 3/8" or smaller washers. MAX. 10 per

fender/wheel opening.

HOOD

MUST BE OPEN AT INSPECTION! So don't come to inspection line with hood bolted down....

1. Can replace front 2 body mounts with 2-1" all thread through the hood, these 2 body mounts cannot be moved, with 4" washers
 - A. Can have a 4" or less spacer free floating between core support and frame.
 - B. Only on the front can you shorten the frame you must leave 3 1/2" in front factory location of the front body mount. This is the body mount that you run your all thread through.
2. Plus 2"x2" angel iron 4" long 1/4" thick back to back 2 on each side of hood, with 1- 1/2" bolt in each or not both 4- 1/2" bolts sheet metal to sheet metal with 4" washers 1/4" thick.
3. Hood must be 100% in stock location and open for inspection.
4. Anything can be removed or cut away but NOTHING can be added
5. Hood must have two (2) holes, at least SIX (6) inches in diameter on each side of carburetor – Not directly on top of carburetor.
6. IF HOOD IS REMOVED, EITHER FAN BLADE MUST BE REMOVED OR FAN BELT MUST BE CUT.
7. A MAX. of 20 - 3/8' bolts/washers or smaller are allowed to bolt together hood seams.

TRUNK—

1. Can replace any of the 4 rear body mounts with 2-1" all thread through the trunk, with 4" washers. Bottom nut and washer may be on bottom side of the frame, not to extend 1" past nut and may extend through trunk. ZERO welding allowed mounting any of these threaded rods
2. Plus (4) 2"x2" angel iron 4" long 1/4" thick back to back, with 1- 1/2" bolt in each or not both (4) - 1/2" bolts sheet metal to sheet metal with 4" washers 1/4" thick.
3. Trunk must be 100% in stock location. Must be on the factory hinges, choices to do your trunk A. stock location OR
 - B. 1/2 cut off OR
 - C. 90'd straight down at the halfway point OR
 - D. "V"d downward at 1/2 way point of the trunk, (rear quarters remain in factory position vertical, straight up and down and rear tail light panel/assembly must remain vertical, straight up and downYOU HAVE 1 OF THE 4 ABOVE CHOICES, NO MIXING AND MATCHING
4. Anything can be removed or cut away but NOTHING can be added

TAILGATE: 4 places with #9 wire.

DOORS

1. Drivers door or with passenger doors may be welded solid. You may weld outside only. You may use 4" x 1/8" straps. All other doors 6 on and 6 off

BODYMOUNTS

1. Body mounts and spacers to remain stock and in place. DO NOT EVEN TOUCH THEM Exception, You may replace a broken one with 1/2" size bolt. Stock body pucks must be in place and all bottom nuts must be inside frame except front and rear all thread. ZERO welding allowed mounting this rod. If changed/replaced you must cut away the factory sheet metal for inspection and use a 3"x3"1/4" washer

top and bottom.

FRAMES

1. NO welding on frames allowed except....
2. If running a used car prior to this derby, you are allowed 4 patch plates max (must be on the outside of the frame). Size 4"x4"x1/4". Must be painted a bright color. So it is easily noticed for the inspectors. AFTER INSPECTION OR HEATS NO WELDING THESE PLATES ON. IF ADDITIONAL PLATES ARE FOUND AFTER INSPECTION – NO MONEY WILL PAID OUT
3. No plates on fresh cars to fix/patch rust holes, unless it's a preran/used car then follow patch plate rule.
4. Only on the front can you shorten the frame you must leave 3 1/2" in front factory location of the front body mount. This is the body mount that you run your all thread through. These 2 body mounts cannot be moved.
5. MAY COLD BEND ONLY
6. If changing front stub, cut 3 inches behind second cross member bolt hole. When replacing, can overlap 2 1/2", able to weld both sides, but no adding extra metal. Must be of the same make and model.
7. If restubbing one side of the frame, you are allowed to cut and fit the new frame flush and weld one pass all the way around (butt – fit – weld). Must be of the same make and model.

- SUSPENSION

1. All suspension must remain car type stock. ZERO aftermarket parts
2. Rear control arms may be changed but must be stock NO SHORTING %100 stock
3. You may use (store bought spring spacers only, no homemade, no spacers on top of the springs).
Front and rear
4. You may have a double strand #9 wire to hold coil spring to rear end and leaf sprung cars may use 4 single strands #9 wire as leaf clamps or factory clamps.
5. You may run a double strand of #9 wire twisted together or 3/8' chain or smaller, behind the rear wheels from frame to frame. No extra mounting component can be used to mount this. Just wrap around frame and twist or bolt it.
6. Factory or aftermarket steering column ok
7. If you're running a 03 or newer must run/use stock/factory cradle.
8. Aftermarket or homemade tie rods allowed must have factory ends. NO HEIMS
9. Can use #9 wire or 3/8" chain on A-arms. No welding to accomplish this

- DRIVETRAIN

1. ANY drivetrain allowed with the following criteria.
2. You may swap engines, i.e... Chevy in a Ford. Factory location only. No cradle swaps
A. ANY ENGINE OR TRANSMISSION MAY BE USED IN ANY CAR, BUT MUST BE MOUNTED IN A STOCK POSITION. ON A V-BLOCK MOTOR, FRONT SPARK PLUGS MUST BE EVEN OR IN FRONT OF UPPER BALL JOINT; ON IN-LINE MOTORS, NUMBER TWO (2) SPARK PLUG MUST BE EVEN OR IN FRONT OF UPPER BALL JOINT.
3. **Factory bottom motor mounts must be used; same goes for tranny factory mount.**
A. Lower aftermarket cradle is allowed (ONLY)

B. NO Pulley Protectors

C. NO "DP" (distributor protector)

D. NO Trans Protectors or Steel Bells

4. Only the lower stock engine mounts may be welded to cradle only. You may use two 1/2" thick 4x4 spacers to raise engine from steering components

5. No tranny protectors/braces, stock mounting only, stock cross members only, you may use a 2"x 2"x 1/4" angel iron 4" long welded only to inside frame rail to mount your stock cross member I.E. CHEVY DRIVE LINE IN A FORD. No other welding

6. You may weld rear end gears / spools ok. - pinion brakes OK

7. REARENDS WILL STAY THE AS 2018, YOU CAN WELD STOCK OEM BRACKETS TO ANY 5 LUG REAREND, Reared swaps allowed no bracing, and no re-enforcement. Max axle size 31 spline, Ford, GM or Mopar Clarification: All must be factory axles(cast flanges) OR YOU MY USE AFTERMARKET 31 SPLINE AXLES MAX SIZE. CAUSE THE FACTORY AXLES ARE GETTING HARDER TO FIND. and rear ends, must be a direct bolt-in, NO fabricating or welding allowed of axles or reared(inside or outside)

8. All money winners will be subject to pull axles before payout at official's discretion

9. You may run 1 spot of #9 wire doubled 4 strands total twisted together or 3/8" chain or smaller from rear end to frame per side, nothing thru body. .

10. Floor shifters allowed, headers allowed, gas pedals and brakes, Clarification: none may strengthen car

11. No pulley or DP protectors of any kind and no aftermarket parts of this nature at all.

12. Engine oil pan and tranny pan protectors ok, flat bottom side only

13. Slip shafts allowed at all shows. A \$100.00 bonus will be paid to the highest placing driver with an OEM car driveshaft.

CAGE AND HALO BAR:

1. You must have a 4 point cage minimum. Two cross bars, one in dash area, and one behind driver's seat that must be no more than 18" from back of driver seat. Two side bars cannot go past dash bar or more than 18" behind driver seat. Get your tape measure out. If your more than 18" you will have to cut.

A. A pipe/tub/square stock or flat plate (metal). Max. 2" wide 1/4" thick, 2"x2"x1/4". Allowed from bottom of side bar to sheet metal only! in driver door area, must be behind inner front door seem and in front of front door rear inner door seem. With a passenger, you may have one on passenger side.

2. Halo bar allowed must be in line with seat bar. NONE of these bars can contact floor or frame

3. Gas tank and Trans cooler protector may be welded to back bar. Must be 5 inches from rear sheet metal (package tray). The area that your upper back seat was from. This bar must be off the floor and must stay inside of interior of rear driver's compartment, IN FRONT OF PACKAGE TRAY.

4. Drivers and passenger doors must be padded.

5. Gas tank and single battery must be moved and secured. Tank behind the seat, Battery centered in the passenger front floor.

6. NO PLASTIC TANKS, unless in a wooden box 1" thick minimum or a metal box 1/4" minimum. All sides except top side. This also goes for if you're using a metal boat tank.

7. Mounted in center of the back side area.

- A. Battery and gas tank must be tight when coming through inspection line or you won't be inspected.
- 8. Nothing may be mounted in a way that strengthens the car.
- 9. Tranny coolers allowed. Must be mounted in back seat area and approved by officials.

BUMPERS:

- 1. You may load inside or back side of bumper. Must still look stock With OEM STOCK outer chrome skin.
- 2. You may weld front and rear bumper strait to frame/hard nose no added metal, only on the front can you shorten the frame you must leave 3 1/2" in front factory location of the front body mount. This is the body mount that you run your all thread through. Use following the rules for the front bumper if using a shock only.
- 3. You may weld bumper bracket(in factory location) to frame 4 inches from the back of bumper, , in addition you may put 4 one inch welds on back side of bumper bracket or to weld shock inside frame(example Crown Vics).
- 4. If your car did not come with a shock (example 71 Chevy) you may use a 74-76 CHEVY CANS welded to factory specs OR BOP bracket bolted/ mounted in stock location with stock bolts.
- 5. You may chain, 2 piece of chain per side bolted or welded (weld one link on each end) from the mount to mount to hold on the bumper.

TIRES: Brakes MUST work.

- 1. Forklift and skid loader tires are allowed
- 2. All wheels and rims must be stock, except you are allowed 7" wheel centers.
- 3. Valve stem protectors are allowed.
- 4. Liquid in tires is allowed. Studs and screws in rims to hold tires in place are allowed

ALL JUDGES DECISIONS ARE FINAL

Any questions contact: Randy Schwartzkopf at [618-218-0203](tel:618-218-0203) call or text or at Randyschwartzkopf@gmail.com